


SUMEC

Phono<sup>®</sup> Solar  
AUSTRALIA

415W  
BIFACIAL

# DIAMOND DUAL GLASS

## BUILT TOUGH TO PERFORM IN AUSTRALIA



## WHY DUAL GLASS MATTERS

### LOWER GRADE, PLASTIC BACKSHEETS

Under harsh conditions, the plastic back sheet has been a common failure point of solar panels in Australia.



### DIAMOND GLASS

A second layer of tempered glass in replacement of the plastic back sheet allows **Zero Vapour Penetration**. This change and the addition of POE means you can install next to the coastline or in Australia's harshest climates.



**25** 25 YEAR  
PRODUCT  
WARRANTY\*



**30 YEAR**  
PERFORMANCE  
WARRANTY




# THE ENGINEERS' CHOICE

Working within Australia's harsh environment, Sumec Phono Solar manufacture a beautifully tough panel that's **simply different**.

## BIFACIAL TECHNOLOGY

### MORE POWER, PER PANEL

The Diamond Dual Glass solar panel can absorb power from both sides of the panel. In optimal install conditions, **up to 30% additional power yield can be gained** thanks to its Bifacial design.



**SALT MIST CERTIFICATION**  
 To the highest Severity Level

**CYCLONE TESTED**  
 Rated for Wind Regions like NT


**INCREASED HAIL TESTING**  
 For increased resilience

## ROBUST DESIGN FOR HARSH AUSTRALIAN CONDITIONS

The Diamond Dual Glass Series is thoroughly tested and built for the extremes. From the high humidity of North Queensland to the Coastal regions where over 80% of Australian's live.

## 20% MORE WARRANTED POWER

The enhanced build quality of the Diamond Dual Glass Panel gives us the confidence to warrant its performance for three decades. **A longer lasting panel is the better choice for the environment.**



BLOOMBERG  
**TIER 1 BRAND**



OWNED BY  
**FORTUNE 500**  
 GLOBAL COMPANY



**2022 TOP PERFORMING PANEL**



**30 YEAR PERFORMANCE WARRANTY**


# MAKE A SECURE INVESTMENT

## 4 LAYERS OF PROTECTION

In 2013 there were more than 400 Solar Panel Manufacturers approved for install in Australia and today there are fewer than 100.

SUMEC Group was founded over 40 years ago so, we understand a warranty is only as strong as the company behind it.

As a **Blue Chip brand**, Sumec Phono Solar has **longevity, commitment and stability** at every layer of protection. From the Fortune 500 Founding Corporation, through to the experienced Australian Distributor, **you can feel secure in your solar investment** for decades to come.



AUSTRALIAN  
OFFICE AND  
REPRESENTATION

SUMEC PHONO SOLAR AUSTRALIA  
Level 35, Tower One, 100 Barangaroo Ave, Sydney, AUSTRALIA  
TEL: 02 8114 4516 [www.phonosolar.com.au](http://www.phonosolar.com.au)

PHONO SOLAR INTERNATIONAL (SUMEC)  
No. 1 Xinghuo Rd., Nanjing Hi-tech Zone, Nanjing, CHINA  
[www.phonosolar.com](http://www.phonosolar.com)





# DIAMOND DUAL GLASS MODULE

## ELECTRICAL TYPICAL VALUES

|                                 |                                     |       |
|---------------------------------|-------------------------------------|-------|
| Model                           | PS415M8GF-18/VH<br>PS415M8GFH-18/VH |       |
| Testing Condition               | STC                                 | NOCT  |
| Rated Power (Pmpp) <sup>2</sup> | 415W                                | 307   |
| Rated Current (Imp)             | 13.32                               | 10.76 |
| Rated Voltage (Vmpp)            | 31.16                               | 28.51 |
| Short Circuit Current (Isc)     | 14.03                               | 10.99 |
| Open Circuit Voltage (Voc)      | 37.32                               | 35.08 |
| Module Efficiency (%)           | 21.25                               |       |

## TEMPERATURE CHARACTERISTICS


|                          |           |
|--------------------------|-----------|
| Voltage Temperature      | -0.30%/°C |
| Coefficient Current Temp | +0.05%/°C |
| Coefficient Power Temp   | -0.38%/°C |
| Power Tolerance          | 0~+5w     |
| NOCT                     | 45±2-C:   |
| Bifaciality              | 70±5%     |

## MECHANICAL CHARACTERISTICS

|                  |                                               |
|------------------|-----------------------------------------------|
| Cell Type        | Monocrystalline 182mm x 91 mm                 |
| Dimensions       | Length: 1722mm, Width: 1134mm<br>Height: 30mm |
| Weight           | 22.0kg                                        |
| Front/Back Glass | 1.6/1.6mm Toughened Glass                     |
| Frame            | Anodised Aluminium Alloy                      |
| Cable            | 1100mm (incl. connector)                      |
| Junction Box     | IP 68 rated                                   |
| Connectors       | EVO2 Connector, MC4                           |

## PACKING CONFIGURATION

|                      |        |        |
|----------------------|--------|--------|
| Container            | 20' GP | 40' GP |
| Pieces per container | 216    | 936    |



## BIFACIAL ELECTRICAL VALUES


| Back Power Gain   | 5%    | 10%   | 15%   | 20%   | 25%   | BNPI  |
|-------------------|-------|-------|-------|-------|-------|-------|
| Pmax/W            | 430   | 444   | 459   | 473   | 488   | 454   |
| Module Efficiency | 22.02 | 22.74 | 23.51 | 24.22 | 24.99 | 23.25 |
| Voc/V             | 37.32 | 37.32 | 37.32 | 37.32 | 37.32 | 37.32 |
| Isc/A             | 14.53 | 15.00 | 15.51 | 15.98 | 16.49 | 15.34 |
| Vmp/V             | 31.16 | 31.16 | 31.16 | 31.16 | 31.16 | 31.16 |
| Imp/A             | 13.80 | 14.25 | 14.73 | 15.18 | 15.66 | 14.57 |

Additional back power gain will vary according to the ground clearance and surface reflectivity at the installation location. Higher ground clearance and surface albedo will provide better results.

## ABSOLUTE MAXIMUM RATING

|                                           |                   |
|-------------------------------------------|-------------------|
| Operating Temperature                     | From -40 to +85°C |
| Hail Diameter @ 97.92km/h                 | Up to 35mm        |
| Maximum Test Load Two Rails (push/pull)   | 5,400Pa/4,000Pa   |
| Maximum Test Load Three Rails (push/pull) | 8,500Pa/6,000Pa   |
| Maximum Series Fuse Rating                | 30A               |
| PV Module Classification                  | II                |
| Module Rating (IEC 61730)                 | C                 |
| Maximum System Voltage                    | DC 1000V/1500V    |

## ELECTRICAL CHARACTERISTICS



- In compliance with our warranty terms and conditions.
- Measurement conditions under irradiance level of Standard Test Conditions (STC): Irradiance 1000W/m<sup>2</sup>, AM 1.5, Cell Temperature 25°C.



30-year linear performance warranty to 84.95% at year 30.  
This amounts to 2% degradation in the first year, 0.45% annually.

\* 25 year Product Warranty applies to Residential System Installations.  
Commercial System Installations are eligible for 15 year Product Warranty.  
Please see our warranty document for full terms, conditions and details.

NOTE: This datasheet is not legally binding. Phono Solar reserves the right to make specifications changes without notice.  
Further information can be found on our website: [www.phonosolar.com.au](http://www.phonosolar.com.au)

Sumec Phono Solar modules are proudly manufactured in our facility in Nanjing, China.